

Download File PDF Ademco 5828 Installation Manual

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler



so many fake sites. this is the first one which worked! Many thanks

Honeywell

ADEMCO 5828/5828V

Wireless Bidirectional Fixed-Word Keyboards

INSTALLATION AND SETUP GUIDE

GENERAL INFORMATION

The ADEMCO 5828 and 5828V are wireless, bidirectional, fixed-word keyboards that may be used in conjunction with IBM PC and XT/AT series microcomputers. 5828V models require one or other of the following: IBM PS/2 Keyboard Adapter or IBM PS/2 Keyboard Adapter for AT. 5828 models require one of either a IBM PS/2 Keyboard Adapter or IBM PS/2 Keyboard Adapter for AT. The 5828/5828V keyboards are not compatible with computer systems that have three-digit serial numbers (e.g., VISTA12345).


- Plug programmable special function keys
 - Roll-over plates for easy removal of the keypad and battery replacement
 - On-board battery monitor (AC adapter kit, ADEMCO P/N 5828M)
 - Battery powered with 3-AAA batteries
- The 5828V keypad additionally provides:
- Menu Message center
 - Menu Message center
 - Menu Message LED indicator
 - Built-in microphone and speaker

NOTES

The 5828/5828V cannot be used as the primary system keyboard, and must not be used to prepare or edit any security system. All systems require a hard-wired keyboard or Computer Controller with one. Once programmed, the 5828/5828V can be used to initiate all system functions of a fixed English keypad.



5828 Keypad with Front Cover Removed



5828V Keypad with Front Cover Removed

- Operation (See NOTE below)**
1. **Battery Powered Operation:** When powered by battery, the keypad activates when any key is pressed. When the PC is powered, the keypad sends a system status request, and displays and/or transmits the present status information for the system.
 2. **AC Powered Operation:** When powered by AC, the keypad remains active at all times. An absence of status indicator will cause the display to automatically turn off. The keypad will automatically return the new status information to the display.
- If AC power is not, the keypad will switch to battery-powered operation and AC power is restored and a new status request is made (M-F).

NOTE: Whether the unit is powered by battery or AC, the 5828/5828V may take up to 3 seconds to display and/or transmit the current status after pressing the M-F key.

WALL MOUNTING: Before mounting the 5828 & 5828V permanently, determine a good RF location as follows:

1. If interfacing to a VDSX panel, try communicating with the panel from different locations.
2. If interfacing to a VDSX panel, perform a Go-No-Go test from the panel. Before the Go-No-Go test, make up the installation and testing guide for the panel.

Local mounting locations in or near large metal objects, since they can decrease the transmission range or block transmission.

- Secure the mounting plate to the wall, using proper sized hardware through the pre-mounting holes.
- Plug the cord from the optional power pack into the keypad's DC input connector, and secure the wires through the wire grommet on the back of the keypad.
- Position the keypad over the mounting plate and slide down, engaging the four retaining clips on the plate with the corresponding clips on the keypad.

DESKTOP MOUNTING: For all purposes, the keypad may be placed in any convenient, RF suitable location and operated in its battery-powered mode, or even as AC, which is powered by the optional Power Pack Adapter, ADEMCO P/N 5828M.

BATTERY INSTALLATION OR REPLACEMENT

CAUTION: Remove the AC/DC power connector from the keypad if applicable, before attempting to install or replace the batteries.

1. Separate the keypad from its mounting plate by adding the keypad up and away from the mounting plate.
2. Open the battery compartment door to expose the batteries.

[Download PDF version of :](#)
Ademco 5828 Installation Manual